



Model	AVANT 630	AVANT 635	AVANT 640
Length	2550 mm	2550 mm	2550 mm
Width (with 26x12.00-12 wheels)	1290 mm	1290 mm	1305 mm
Height	2020 mm	2020 mm	2035 mm
Weight	1500 kg	1530 kg	1590 kg
Standard wheels	26x12.00-12" grass/TR	26x12.00-12" grass/TR	26x12.00-12" grass/TR
Transmission, drive	hydrostatic	hydrostatic	hydrostatic
Auxiliary hydraulics oil flow / pressure	44 l/min 200 bar	66 l/min 200 bar	66 l/min 200 bar
Turning radius inside/outside	900 / 2190 mm	900 / 2190 mm	900 / 2190 mm
Max. lifting height	2820 mm	2820 mm	2835 mm
Max. lifting capacity (hydr.)	1400 kg	1400 kg	1400 kg
Max. tipping load*	1100 kg	1100 kg	1100 kg
Max. breakout force / 50 cm	1250 kg	1250 kg	1250 kg
Engine make and type	Kubota D1105	Kubota V1505	Kubota V1505
Engine output (ISO Gross)	21 kW (28 hp)	28 kW (37,5 hp)	28 kW (37,5 hp)
Fuel	diesel	diesel	diesel

*with counterweights

Pulling force

Model	Hydraulic motor Tyre size	Drive speed	Pulling force
630/635	OMT 315	17 km/h	900 kp
	OMT 400	14 km/h	1100 kp
	OMT 500	11 km/h	1400 kp
640	320/55-15 HD	22 km/h	1400 kp
640	26x12.00-12"	22 km/h	1400 kp

Width

Wheel size	Width 630/635	Width 640
27 x 8.50 - 15	990 mm	1005 mm
26 x 12.00 - 12	1290 mm	1305 mm
320/60 - 12	1290 mm	1305 mm