

# ISOLI ..... PT 160



Altezza max. di lavoro  
Max. Working height  
Max. Arbeitshöhe

16 m

Sbraccio max. di lavoro  
Max. Working boom extension  
Max. Arbeitsaulandung

8,9 R+A

Portata  
Capacity  
Tragfähigkeit  
max 250 kg

N° operatori  
N° operators  
N° de Arbeiter  
2

Forza manuale max.  
Max. manual force  
Max. Handkraft  
40 daN

Velocità max. vento  
Max. wind speed  
Max. Windgeschwindigkeit

12.5 m/s

Braccio di lavoro  
Working boom  
Arbeitsarm

Braccio telescopico a 3 sezioni  
Telescopic and 3 section element

Angolo braccio  
Boom angle  
Armwinkel  
-25°/+75°

Rotazione sovrastruttura  
Upperstructure rotation  
400°

Piattaforma  
Platform  
Hubarbeitsbühne  
Alluminio 1390x715x1115 mm  
Aluminium 1390x715x1115 mm

Rotazione piattaforma  
Platform rotation  
Drehung des Hubarbeitsbühne  
Idraulica 90°dx+ 90°sx  
Hydraulic 90°RH+ 90°LH


Livellamento piattaforma  
Platform levelling  
Nivellierung der Hubarbeitsbühne  
Idraulico  
Hydraulic


Stabilizzatori  
Outriggers  
Abstützungen  
Idraulici, verticali ant./post.  
Hydraulic, "H" type at front/rear


Scartamento minimo stab.  
Outriggers minimum width  
Spurweite Abstützungen min./max.  
Anteriore 1.950 m - Posteriore 2.010 m  
Front 1.950 m - Rear 2.010 m

Comandi  
Controls  
Steuerungen  
idraulici  
hydraulic

Installazione minima  
Minimum installation  
Mindeste Installation  
MTT 3,5 t  
TWG 3,5 t

A=  MAX  
250 kg

C=  MAX  
120 kg

B=  MAX  
200 kg

D=  MAX  
80 kg

